```
ASHLAND CHEMICAL -- PO POLYPRO HIMONT 7823 NATURAL L - THERMOPLASTIC RESIN
MATERIAL SAFETY DATA SHEET
NSN: 685000F010781
Manufacturer's CAGE: 34897
Part No. Indicator: A
Part Number/Trade Name: PO POLYPRO HIMONT 7823 NATURAL L
______
                      General Information
______
Item Name: THERMOPLASTIC RESIN
Company's Name: ASHLAND CHEMICAL COMPANY Company's P. O. Box: 2219
Company's City: COLUMBUS
Company's State: OH
Company's Zip Code: 43216
Company's Emerg Ph #: (606) 324-1133
Company's Info Ph #: (614) 909-3333
Record No. For Safety Entry: 001
Tot Safety Entries This Stk#: 001
Date MSDS Prepared: 27APR88
Safety Data Review Date: 15JUN90
Preparer's Company: ASHLAND CHEMICAL COMPANY
Preparer's City: COLUMBUS
Preparer's State: OH
Preparer's Zip Code: 43216
MSDS Serial Number: BHTGZ
______
              Ingredients/Identity Information
______
Proprietary: NO
Ingredient: ETHYLENE PROPYLENE COPOLYMER Ingredient Sequence Number: 01
Percent: 100%
NIOSH (RTECS) Number: 1001979EP
CAS Number: 9010-79-1
______
               Physical/Chemical Characteristics
______
______
                Fire and Explosion Hazard Data
______
Flash Point: >300F
Extinguishing Media: FOAM, WATER FOG, CO2, DRY CHEMICAL. WATER MAY BE USED
TO KEEP FIRE-EXPOSED CONTAINERS COOL UNTIL FIRE IS OUT.
Special Fire Fighting Proc: WEAR SELF-CONTANIED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE DEMAND MODE & FULL BODY
PROTECTION WHEN FIGHTING FIRES.
Unusual Fire And Expl Hazrds: DUST MAY BE AN EXPLOSION HAZARD.
_______
                      Reactivity Data
______
Stability: YES
Materials To Avoid: STRONG OXIDIZING AGENTS
Hazardous Decomp Products: CO2, CO, TOXIC MATERIALS
Hazardous Poly Occur: NO
______
                     Health Hazard Data
______
Route Of Entry - Inhalation: NO
Route Of Entry - Skin: YES
Route Of Entry - Ingestion: NO
Health Haz Acute And Chronic: SKIN: CONTACT WITH MOLTEN MATERIAL WILL
CAUSE THERMAL BURNS.
Carcinogenicity - NTP: NO
Carcinogenicity - IARC: NO Carcinogenicity - OSHA: NO
Explanation Carcinogenicity: NONE
Signs/Symptoms Of Overexp: SKIN: CONTACT WITH MOLTEN MATERIAL WILL CAUSE
THERMAL BURNS.
Emergency/First Aid Proc: SKIN: FLUSH W/COLD WATER. GET MED ATTN.
_______
             Precautions for Safe Handling and Use
______
Steps If Matl Released/Spill: SMALLS: SWEEP UP MATERIAL ONTO PAPER. LARGE
SPILL: SHOVEL MATERIAL INTO CONTAINERS. THOROUGHLY SWEEP AREA OF SPILL TO
CLEAN UP ANY RESIDUAL MATERIAL.
Waste Disposal Method: DEPOSIT/DISPOSE OF IN A LANDFILL IN ACCORDANCE WITH
LOCAL, STATE, & FEDERAL REGULATIONS.
Precautions-Handling/Storing: CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS
WHEN EMPTIED, SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES, VAPOR,
```

ASHLAND CHEMICAL -- PO POLYPRO HIMONT 7823 NATURAL L - THERMOPLASTIC RESIN

LIQUID & SOLID. ______ Control Measures ______ Respiratory Protection: NOT REQUIRED UNDER NORMAL CONDITIONS OF USE. Ventilation: NOT REQUIRED UNDER NORMAL CONDITIONS OF USE. Protective Gloves: RESISTANT Eye Protection: SAFETY GLASSES Other Protective Equipment: NORMAL WORK CLOTHING COVERING ARMS & LEGS. ______ Transportation Data ______ ______ Disposal Data ______ ______ Label Data Label Required: YES Label Status: G Common Name: PO POLYPRO HIMONT 7823 NATURAL L Special Hazard Precautions: SKIN: CONTACT WITH MOLTEN MATERIAL WILL CAUSE

THERMAL BURNS. SKIN: CONTACT WITH MOLTEN MATERIAL WILL CAUSE THERMAL BURNS.

Label Name: ASHLAND CHEMICAL COMPANY Label P.O. Box: 2219
Label City: COLUMBUS
Label State: OH

Label Zip Code: 43216 Label Emergency Number: (606) 324-1133