## Reprocessed UHMW

Ultra High Molecular Weight Polyethylene



Reprocessed UHMW polyethylene utilizes recycled UHMW in its composition, making it a greener and more economical alternative in applications where virgin UHMW is not essential. Reprocessed UHMW sheet serves as a cost-effective alternative to virgin grade UHMW, providing excellent value when it comes to applications that do not require FDA approval.

Reprocessed UHMW-PE offers all the same benefits of standard UHMW-PE sheets but at a much more cost-effective price. It has the same low coefficient of friction as standard UHMW while also offering slightly better wear resistance. Reprocessed UHMW is self-lubricating and a great alternative to metals that require external lubrication like grease or oil. Internal lubrication greatly extends part life and contributes to its extremely low coefficient of friction.

## Applications and Uses

Reprocessed UHMW can be fabricated for use where excellent wear properties are required, such as conveyor guard rails, guide shoes, belt scrapers, suspension wear plates, idler rollers, and chute, hopper, and bin liners. Reprocessed UHMW can also be used for smaller mechanical parts.

- · Conveyor guard rails
- · Belt scrapers,
- Suspension wear plates
- Idler rollers
- · Guide shoes
- · Wear strips
- Sprockets
- Bushings
- Housings
- Wheels
- Bearings
- Component parts
- Pinion gears
- Flanged rollers



Properties and Specifications	
Density	Reprocessed
Tensile strength at yield 73°F	.935
Elongation 73°F	3000
*Relative volumetric abrasion loos	290
Confficient of friction 73°F on steel	.17- 20 .10- 20
Izod Impact Strength 73°F	96
Hardness 73°F	D 63 - 69
Melting point	275° - 280°
Coefficient of linearthermal expansion	1.9 x 10 <sup>4</sup>
Continuous service temperature in air (max)	180
Volume resistivity	>1015
Dielectric constant (103 Hz)	_
Dielectric strength	900

330 Commerce Circle Sacramento, CA 95815 (888) 768-5759



For more information, go to www.P65Warnings.ca.gov.

